



Material Safety Data Sheet - Quickson Pantone Colors
Date 11-30-2006

		H	M	I	S		
		Hazard Ratings				Health	1
Minimal	0	Serious	3	Flammability		1	
Slight	1	Severe	4	Reactivity		0	
Moderate	2						

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Van Son Holland Ink Corporation of
America
185 Oval Drive, Islandia NY 11749
Emergency Telephone: 631-715-7000
Product Class: Offset Ink Oxidizing
Trade Name: Quickson Plus Colors

Chemtrec 24 Hour Emergency No-800-424-9300
Manufacturer s Code ID: VS91100-91115, VS91300-91315
VS931-935

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Organic Pigments	See Table 2	15-30	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oils	8001 Various	23-35	N/A	N/A	No
Severe Hydrotreated Petroleum Middle Distillate	64742-46-7	10-15	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	5-10	15mg/M3	N/A	No
Manganese Drier	8030-70-4	0-1	5mg/M3	N/A	No
Cobalt Tallate	61789-52-4	0-1	0.1mg/M3	N/A	IARC

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910 . . . Cobalt Compounds, Manganese Compounds, Treated Middle Distillate

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact Direct contact may cause irritation.
 Skin Contact Prolonged contact or repeated exposure may cause minor irritation.
 Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation
 of nasal and respiratory passages.
 Ingestion May cause gastrointestinal irritation.
 Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.
 Target Organs: Skin, eyes, lungs.
 Primary Routes of entry Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

Eye Contact Flush with large amounts of water until irritation subsides.
 If irritation persists, contact a physician.
 Skin Contact: Wash with soap and water. Remove contaminated clothing and wash
 thoroughly before reusing.
 Ingestion If swallowed, do not induce vomiting. Call a physician.
 Inhalation Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point Above 250 F Method used: closed cup
 Explosion Limits LEL: N/A UEL: N/A
 Extinguishing Media Foam, carbon dioxide, dry chemical. Water spray may be
 applied to cool exposed closed containers.
 Unusual Fire and Explosion Hazards Dense smoke may be generated when burning. Carbon
 Monoxide and Carbon Dioxide generated as combustion products

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers.
 If petroleum hydrocarbon is used, provide sufficient ventilation.
 Waste Disposal Method: Dispose of in accordance with Federal, State and local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use.
Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. Eye Protection: Goggles recommended.
Protective Gloves: Vinyl Gloves recommended. Other Protection: None required.
Respiratory Protection: None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs)	1.10-1.30 lbs./gallon	90-150 Grams/liter Method 24
Boiling Range °F: > 500		Freezing Point °F: N/A
Vapor Density vs. Air: Heavier		Vapor Pressure: less than 0.04psi
Density: 8.40-8.80 lbs./gallon	ASTM D1475	Specific Gravity: 1.00-1.03
Type of Odor: Oily		Odor Threshold: N/A
Appearance: Colored viscous paste.		pH: N/A
Evaporation Rate vs. Butyl Acetate: Slower		Coefficient of Water/oil Distribution: N/A
Percentage Volatile By Weight: 10-15%	ASTM D2369	

10. STABILITY AND REACTIVITY

Product Stability: Stable
Conditions to Avoid: Strong oxidizing agents. Avoid storage above 90 F.
Keep containers closed when not in use.
Hazardous Decomposition Products: None.
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by OSHA or the National Toxicology Program (NTP). The International Agency for Research on Cancer (IARC) lists cobalt compounds as possible human carcinogens (Class 2B.)
Mutagen No
Teratogen No
Reproductive Toxicity No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act) All ingredients listed in TSCA Inventory
CERCLA Superfund 40CFR 117.302 Contains no reportable materials
SARA Title III 1% Cobalt Compound.
Barium Compounds present. Request Table 1.
FDA This printing ink is not a food additive and would not have approval for direct or indirect contact with food.
EINECS (European Economic Community) All ingredients listed
California Proposition 65 Pigment Red 53.1. Request Table 1.
CONEG Legislation Meets all current State and Heavy Metal limitations.
Canadian WHMIS Controlled product
Vegetable Ink Printing Act of 1994 Meets the 20% minimum requirement of vegetable oil in sheet fed inks.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.