P/N'S SP-11019



Material Safety Data Sheet - SonaPrint Colors Date 06/30/2010

	H	M	I	S	
	Hazard	Ratings		Health	1
Minimal	0	Serious Severe	3	Flammability	1
Slight Moderate	2	pevere	4	Reactivity	0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America

185 Oval Drive Islandia, NY 11749

Emergency Telephone: 631-715-7000
Product Class: Of feet Ink Oxidizing
Trade Name: SonaPrint Colors

MANUFACTURER:

Van Son Royal Dutch Printing Ink Factories,

Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: VS829 - 849, VS 851- 853

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Organic Pigments	See Table 2	15-25	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oil Includes	Various	10-20	N/A	N/A	No
Linseed Oil	8001-26-1				
Soy Oil	8001-22-7				
Severe Acid Treated	64742-13-8				
or Solvent Refined Middle Distillate	64741-91-9	20-40	5mg/M3	N/A	No
Cobalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	8030-70-4	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2-4	N/A	N/A	No

3. HAZARDS IDENTIFICATION

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE				
Eye Contact				
Skin Contact				
Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or inritation				
of nasal and respiratory passages.				
Ingestion				
Medical Conditions aggravated by normal exposure: Persons with demnatitis should avoid skin contact.				
Target Organs:Skin, eyes, lungs.				
Primary Routes of entry				
EMERGENCY FIRST AID PROCEDURES				
Eye Contact				
If initation persists, contact a physician.				
Skin Contact:				
thoroughly before reusing.				
Ingestion				
Inhalation				

5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	LEL: N/A UEL: N/A
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: W ipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient vertilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling:

Avoid storage above 90 F. Keep containers closed when not in use.

Other Precautions:

None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:

Use sufficient ventilation.

Eye Protection:

Goggles recommended.

Protective Gloves:

Gloves recommended.

Other Protection:

None required.

Respiratory Protection:

None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.10-2.30 lbs./gallon

Boiling Range °F:> 500

Vapor Density vs. Air: Heavier

8.5-8.85 lbs./gallon ASTM D1475

Type of Odor: Oily

Appearance: Colored viscous paste.

Evaporation Rate vs. Butyl Acetate: Slower

Percentage Volatile By Weight: 23-27% ASTM D2369

240-260 Grams/liter Method 24

Freezing Point °F: N/A

Vapor Pressure: less than 0.04ps.

Specific Gravity: 1.00-1.05 Odor Threshold: N/A

pH: N/A

Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability:

Stable

Conditions to Avoid:

Strong oxidizing agents Avoid storage above 90 F.

Keep containers closed when not in use.

Hazardous Decomposition Products None. Hazardous Polymerization: Will not conur.

11. TOXICOLOGICAL INFORMATION

National Toxicology Program (NTP). The International Agency for Research on

Cancer (IARC) lists cobalt compounds as possible human carcinogens (Class 2B.)

Mutagen

TeratogenNo Reproductive TaxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION-DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)All ingredients listed in TSCA Inventory

CERCLA Superfund 40CFR 117.302 Contains no reportable materials

Barium Compounds present. Request Table 1.

This printing ink is not a food additive and would not have

direct or indirect contact with food. EINECS (European Economic Community) All ingredients listed.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.