

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard Rule – 29CFR 1910.1200 and the Canadian Hazardous Products Act



SECTION 1. Identification

GHS SDS Date 5/29/2015 Version 1.0

Product Code 4-1172, 4-1175, 4-1175-5, 4-1175-55

Product Name: ABDick Isopropyl Alcohol 99%

Mark Andy Print Products

201 W Oakton Avenue Des Plaines IL 60018 <https://shop.markandy.com>

Ph. 800-225-4835 (USA) 800-387-3143(Canada) Fax 800-447-1231 for product information

24 Hour Emergency telephone number: CHEMTREC: 1-800-424-9300

NOTE: CHEMTREC emergency number to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

SECTION 2. Hazard(s) Identification

*** EMERGENCY OVERVIEW ***: Highly flammable liquid and vapor.

GHS Classification

Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 2

H225 Highly flammable liquid and vapor.

Eye Irritation, category 2

H319 Causes serious eye irritation.

STOT, single exposure, category 3, NE

H336 May cause drowsiness or dizziness.

GHS PRECAUTIONARY STATEMENTS

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Nonsmoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P312 Call a POISON CENTER/doctor/physician if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use appropriate method to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
2-propanol	67-63-0	75-100	GHS02-GHS07	H225-319-336

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4.

First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5.

Fire-Fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Highly flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Use water spray to knock down vapors. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6.

Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. If leak or spill has not ignited, use water spray to disperse the vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 7.

Handling and Storage



HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight.

SECTION 8.

Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
2-propanol	200 ppm	400 ppm	400 ppm	N.D.

Personal Protection

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.

SKIN PROTECTION: Wear impervious protective gloves. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9.

Physical and Chemical Properties

Appearance: Clear, colorless liquid
Odor: Typical
Density, g/cm³: 0.790
Freeze Point, °F: N.D.
Solubility in Water: Soluble
Boiling Range, °F: 180 - 181
Evaporation Rate: 2.88 (n-Bu Acetate=1)
Vapor Density: 2.08

Physical State: Liquid
Odor Threshold: N.D.
pH: N.D.
Viscosity: N.D.
Explosive Limits, vol%: 2.0 - 12.0
Flash Point, °F: 53
Auto-ignition Temp., °F: N.D.
Vapor Pressure: 32.25 mm Hg @ 20C

(See "Other information" Section for abbreviation legend)

SECTION 10.

Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Avoid contact with caustics. Prevent contact with inorganic acids. Prevent contact with aldehydes. Avoid contact with chlorinated compounds. Prevent contact with halogens. Prevent contact with strong oxidizing agents. Avoid contact with amines.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11.

Toxicological Information

Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Moderately irritating to the eyes causing transient corneal injury.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful or fatal if liquid is aspirated into lungs. Incidentally swallowing small amounts as a result of normal handling operations is not likely to cause injury; however, swallowing larger amounts may cause injury. Overexposure may cause nausea, diarrhea, and/or vomiting. May cause central nervous system depression.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Vapors irritating to eyes and respiratory tract. A component of this product is a potential hazard to the fetus.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50, mg/kg	Dermal LD50, mg/kg	Vapor LC50, mg/L
67-63-0	2-propanol	5,840	>12,800	>9988.0

SECTION 12.

Ecological Information

ECOLOGICAL INFORMATION: No Information

SECTION 13.

Disposal Considerations



Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. If leak or spill has not ignited, use water spray to disperse the vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 14.

DOT Proper Shipping Name:

DOT Hazard Class:

DOT UN/NA Number:

Transport Information

Isopropanol

3

UN1219

Packing Group:

II

Hazard SubClass:

No Information

Resp. Guide Page:

129

SECTION 15.

Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

SECTION 16. Other Information

Datasheet produced by: EH&S - Regulatory Department

HMIS Ratings:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: X

Volatile Organic Compounds, gr/ltr: 100

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, MARK ANDY PRINT PRODUCTS MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons Mark Andy Print Products , Mark Andy Inc. does not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.